



Sizing Chart: Gallium Pro Disc

| Saddle Height | Suggested Size | A | B | C | | D | | C | | D | | E | |
|---------------|----------------|-----------------|-----------------|---------------|-----------|----------------|-----------|----------------|-----------|--------------|--------------|---|--|
| | | Seat Tube Angle | Top Tube Length | Stack | Reach | Stack | Reach | Stack | Reach | Minimum Drop | Maximum Drop | | |
| | | | | 3D Spacer = 0 | | 3D Spacer = 15 | | 3D Spacer = 25 | | | | | |
| 61 | XXS | 75.5 | 499 | 474 | 374 | 488 | 369 | 498 | 366 | -4 | -53 | | |
| 62 | XXS | 75.5 | 499 | 474 | 374 | 488 | 369 | 498 | 366 | -14 | -63 | | |
| 63 | XXS | 75.5 | 499 | 474 | 374 | 488 | 369 | 498 | 366 | -23 | -73 | | |
| 64 | XXS | 75.5 | 499 | 474 | 374 | 488 | 369 | 498 | 366 | -33 | -82 | | |
| 65 | XXS / XS | 75.5 / 74.5 | 499 / 519 | 474 / 492 | 374 / 382 | 488 / 506 | 369 / 377 | 498 / 516 | 366 / 374 | -43 / -23 | -92 / -73 | | |
| 66 | XXS / XS | 74.5 | 499 / 519 | 474 / 492 | 374 / 382 | 488 / 506 | 369 / 377 | 498 / 516 | 366 / 374 | -52 / -33 | -102 / -82 | | |
| 67 | XS | 75.5 | 519 | 492 | 382 | 506 | 377 | 516 | 374 | -42 | -92 | | |
| 68 | XS | 75.5 | 519 | 492 | 382 | 506 | 377 | 516 | 374 | -52 | -101 | | |
| 69 | XS / S | 74.5 / 74 | 519 / 539 | 492 / 523 | 382 / 389 | 506 / 537 | 377 / 384 | 516 / 547 | 374 / 381 | -62 / -28 | -111 / -77 | | |
| 70 | XS / S | 74.5 / 74 | 519 / 539 | 492 / 523 | 382 / 389 | 506 / 537 | 377 / 384 | 516 / 547 | 374 / 381 | -71 / -37 | -121 / -87 | | |
| 71 | S | 74 | 539 | 523 | 389 | 537 | 384 | 547 | 381 | -47 | -96 | | |
| 72 | S | 74 | 539 | 523 | 389 | 537 | 384 | 547 | 381 | -56 | -106 | | |
| 73 | S / M | 74 / 73.5 | 539 / 559 | 523 / 552 | 389 / 395 | 537 / 566 | 384 / 391 | 547 / 575 | 381 / 388 | -66 / -34 | -115 / -83 | | |
| 74 | S / M | 74 / 73.5 | 539 / 559 | 523 / 552 | 389 / 395 | 537 / 566 | 384 / 391 | 547 / 575 | 381 / 388 | -76 / -43 | -125 / -93 | | |
| 75 | M | 73.5 | 559 | 552 | 395 | 566 | 391 | 575 | 388 | -53 | -102 | | |
| 76 | M | 73.5 | 559 | 552 | 395 | 566 | 391 | 575 | 388 | -62 | -112 | | |
| 77 | M / L | 73.5 / 73 | 559 / 577 | 552 / 575 | 395 / 401 | 566 / 590 | 391 / 396 | 575 / 599 | 388 / 394 | -72 / -44 | -122 / -94 | | |
| 78 | M / L | 73.5 / 73 | 559 / 577 | 552 / 575 | 395 / 401 | 566 / 590 | 391 / 396 | 575 / 599 | 388 / 394 | -82 / -54 | -131 / -103 | | |
| 79 | L | 73 | 577 | 575 | 401 | 590 | 396 | 599 | 394 | -63 | -113 | | |
| 80 | L | 73 | 577 | 575 | 401 | 590 | 396 | 599 | 394 | -73 | -123 | | |
| 81 | L / XL | 73 / 72.5 | 577 / 596 | 575 / 596 | 401 / 408 | 590 / 610 | 396 / 404 | 599 / 620 | 394 / 401 | -83 / -59 | -132 / -108 | | |
| 82 | L / XL | 73 / 72.5 | 577 / 596 | 575 / 596 | 401 / 408 | 590 / 610 | 396 / 404 | 599 / 620 | 394 / 401 | -92 / -68 | -142 / -118 | | |
| 83 | XL | 72.5 | 596 | 596 | 408 | 610 | 404 | 620 | 401 | -78 | -128 | | |
| 84 | XL | 72.5 | 596 | 596 | 408 | 610 | 404 | 620 | 401 | -87 | -137 | | |
| 85 | XL | 72.5 | 596 | 596 | 408 | 610 | 404 | 620 | 401 | -97 | -147 | | |

This chart indicates recommended values. Max and min drop values are calculated according to Canadian specifications. Please consult one of our authorized dealers for further informations on your bike fit.



ARGON 18