



Sizing Chart: Gallium Pro Disc

Saddle Height	Suggested Size	A	B	C		D		C		D		E	
		Seat Tube Angle	Top Tube Length	Stack	Reach	Stack	Reach	Stack	Reach	Minimum Drop	Maximum Drop		
				3D Spacer = 0		3D Spacer = 15		3D Spacer = 25					
61	XXS	75.5	499	474	374	488	369	498	366	-4	-53		
62	XXS	75.5	499	474	374	488	369	498	366	-14	-63		
63	XXS	75.5	499	474	374	488	369	498	366	-23	-73		
64	XXS	75.5	499	474	374	488	369	498	366	-33	-82		
65	XXS/XS	75.5 / 74.5	499 / 519	474 / 492	374 / 382	488 / 506	369 / 377	498 / 516	366 / 374	-43 / -23	-92 / -73		
66	XXS/XS	74.5	499 / 519	474 / 492	374 / 382	488 / 506	369 / 377	498 / 516	366 / 374	-52 / -33	-102 / -82		
67	XS	75.5	519	492	382	506	377	516	374	-42	-92		
68	XS	75.5	519	492	382	506	377	516	374	-52	-101		
69	XS/S	74.5 / 74	519 / 539	492 / 523	382 / 389	506 / 537	377 / 384	516 / 547	374 / 381	-62 / -28	-111 / -77		
70	XS/S	74.5 / 74	519 / 539	492 / 523	382 / 389	506 / 537	377 / 384	516 / 547	374 / 381	-71 / -37	-121 / -87		
71	S	74	539	523	389	537	384	547	381	-47	-96		
72	S	74	539	523	389	537	384	547	381	-56	-106		
73	S/M	74 / 73.5	539 / 559	523 / 552	389 / 395	537 / 566	384 / 391	547 / 575	381 / 388	-66 / -34	-115 / -83		
74	S/M	74 / 73.5	539 / 559	523 / 552	389 / 395	537 / 566	384 / 391	547 / 575	381 / 388	-76 / -43	-125 / -93		
75	M	73.5	559	552	395	566	391	575	388	-53	-102		
76	M	73.5	559	552	395	566	391	575	388	-62	-112		
77	M/L	73.5 / 73	559 / 577	552 / 575	395 / 401	566 / 590	391 / 396	575 / 599	388 / 394	-72 / -44	-122 / -94		
78	M/L	73.5 / 73	559 / 577	552 / 575	395 / 401	566 / 590	391 / 396	575 / 599	388 / 394	-82 / -54	-131 / -103		
79	L	73	577	575	401	590	396	599	394	-63	-113		
80	L	73	577	575	401	590	396	599	394	-73	-123		
81	L/XL	73 / 72.5	577 / 596	575 / 596	401 / 408	590 / 610	396 / 404	599 / 620	394 / 401	-83 / -59	-132 / -108		
82	L/XL	73 / 72.5	577 / 596	575 / 596	401 / 408	590 / 610	396 / 404	599 / 620	394 / 401	-92 / -68	-142 / -118		
83	XL	72.5	596	596	408	610	404	620	401	-78	-128		
84	XL	72.5	596	596	408	610	404	620	401	-87	-137		
85	XL	72.5	596	596	408	610	404	620	401	-97	-147		

This chart indicates recommended values. Max and min drop values are calculated according to Canadian specifications. Please consult one of our authorized dealers for further informations on your bike fit.